



Ultraleather® | Pro



Ink and denim resistant • EPA-registered antimicrobial protection



Ink & Stain Resist




Antimicrobial

Ultraleather® | Pro



554-3353 Tundra




554-3811 Swan



554-3595 Cork



554-3087 Woodcres



554-2661 Blue Bird



554-4443 Laurel



554-3803 Parfait



554-3444 Toasted Bagel



554-7200 Blush




554-2522 Capri




554-4453 Persian Green



554-3352 Shore




554-5241 Butternut



554-1357 Cranberry




554-2530 Sky




554-4530 Coastal



554-5733 Mortar



554-8229 Campfire




554-1329 Rhubarb



554-9395 Violet




554-2711 Blueberry



554-5626 Char



554-3214 Chestnut



554-3209 Cougar




554-9336 Aubergine




554-2547 Sailor



554-5618 Dark Knight



554-3376 Dark Chocolate



554-0008 White Wash



554-5216 Butterfly



554-5649 Ember



554-5648 Cloud



554-4478 Sea Mist



Ultraleather® | Pro

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
100% Reinforced Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard
Approx. 330 Grams Per Square Metre

Thickness:

Approx. 0.95 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 500,000 Double Rubs (Wyzenbeek)*
BS 2543 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Antimicrobial: ASTM E2180

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

Certificates and Standards

- SCS Indoor Advantage Gold Certified
 - Meets stringent chemical emission limits for various VOCs (eg. Formaldehyde)
 - Promotes healthier indoor air quality
 - Contributes towards satisfying credits under LEED® and BIFMA
 - Compliant with California Section 01350

Ultraleather | Pro Resists:

- Ballpoint ink
- Blood
- Mustard and Ketchup
- Betadine
- Denim*
- Red Wine

* Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on our fabrics, cleaning and care instructions, please visit our website.

