



Ultraleather® | Pro



Ultraleather® | Pro is crafted with passion and purpose. Imbued with optimal durability, protection and ease of care attributes, **Pro** maintains the Ultraleather reputation as the softest in its class, and is infused with comfort and power combined. Added features include exceptional abrasion resistance, repellency of most stubborn stains like ink, denim dye, red wine, mustard and iodine-based liquids, along with EPA-registered antimicrobial protection. An extensive color palette provides numerous options for upholstery applications.

Distinctive Characteristics:

- Superior durability - industry leading 14+ weeks hydrolysis results
- Reinforced rayon backing
- 500,000 double rubs (Wyzenbeek), 200,000 rubs (Martindale)
- Bleach cleanable (1:5 bleach/water solution)
- EPA-registered antimicrobial protection does not contain triclosan and triclocarban
- SCS Indoor Advantage Gold Certification

Providing hard-working upholstery solutions - the Ultraleather® family redefines performance fabrics with classic aesthetics and authentic softness.



Ultraleather® | Pro

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
100% Reinforced Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard
Approx. 330 Grams Per Square Metre

Thickness:

Approx. 0.95 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 500,000 Double Rubs (Wyzenbeek)*
BS 2543 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Antimicrobial: ASTM E2180

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

Certificates and Standards

- SCS Indoor Advantage Gold Certified
 - Meets stringent chemical emission limits for various VOCs (eg. Formaldehyde)
 - Promotes healthier indoor air quality
 - Contributes towards satisfying credits under LEED® and BIFMA
 - Compliant with California Section 01350

Ultraleather | Pro Resists:

- Ballpoint ink
- Blood
- Mustard and Ketchup
- Betadine
- Denim*
- Red Wine

* Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on our fabrics, cleaning and care instructions, please visit our website.

